

## MILITARY SPECIFICATION SHEET

SWITCH, ROTARY, OPEN CONSTRUCTION,  
1/2 AMPERE, STYLE SRO9

This amendment forms a part of MIL-S-3786/9D, dated 14 August 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 4

REQUIREMENTS: Delete and substitute:

Angle of throw: 15° and 30° (see table V)

Table II: Delete and substitute:

TABLE II. Electrical loads

Environmental condition	Inductive Load Per MIL-I-81023		Resistive Load	
	Milliamperes	Volts, dc	Milliamperes	Volts
At atmospheric pressure	50	28	500	28 dc
			250	115 V rms
			50	300 V rms
At reduced barometric pressure	--	--	350	28 dc
			100	115 V rms

## CONCLUDING MATERIAL

## Custodians:

Army - ER  
Navy - EC  
Air Force - 85

Preparing activity:  
Air Force - 85

(Project 5930-1430-02)

## Review activities:

Army - MI  
Navy - AS, OS  
Air Force - 11, 99  
DLA - ES

## User activities:

Army - AT, AV, ME, SM  
Navy - CG, MC  
Air Force - 19

AMSC N/A

1 of 1

FSC 5930

DISTRIBUTION STATEMENT A, Approved for public release; distribution is unlimited.